

iD CLICK ULTIMATE


TECHNICAL DATA

Certification & classification	Standards	iD Click Ultimate
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 34 Industrial: 43
Technical characteristics		
Total thickness	EN ISO 24346	6,5 mm
Wear layer thickness	EN ISO 24340	0,7 mm
Total weight	EN ISO 23997	11,3 kg/m ²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342	Planks 176 x 1213 mm 6 planks/box = 1,28 m ² Tiles 300 x 600 mm 7 tiles/box = 1,26 m ²
Surface treatment (PUR)		Yes - PUR Ultimate
Beveled edges		Yes - 4 Bevels
Technical performances		
Dimensional stability	EN ISO 23999	Average measured value 0,05% Required value ≤ 0.15%
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Reaction to fire	EN 13501-1	B _n -s1
Residual indentation	EN ISO 24343-1	≤ 0,05 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL _w up to 19 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)
Thermal resistance	EN ISO 10456	0,05 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Very Good
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0,30
Electrical properties	EN 1815	≤ 2 kV
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C

The above information is subject to modification for the benefit of further improvement. (01/18).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF: 4820 5000 00



Produced under license from I4F
<https://i4f-patents.com>